

C

CINTAS LED

CINTALED01
CINTALED02
CINTALED03
CINTALED04
CINTALED05
CINTALED06
CINTALED07
CINTALED08
CINTALED09
CINTALED10
CINTALED11
CINTALED12
DRIVER01
DRIVER02
DRIVER03
DRIVER04
DRIVER05
DRIVER06

CINTA LED



Cintas Led en rollos de 5m

Características:

Tipo de Led: 3528 o 5050 SMD

Color Fondo Cinta: Blanco

Flujo Luminoso (Lm):


- 3528 SMD: Alto 7-8 Lm, medio 5-6 Lm o bajo 4 Lm
- 505 SMD: Alto 18-21 Lm, medio 16-18 Lm o bajo 12-15 Lm

Colores:

- Cálido (WW) 2700-3300°K
- Neutro (WW) 4000-4500°K
- Frío (CW) 6000°K

Grado de protección: 20/65

Voltaje: 12V



CÓDIGO	TIPO LED	W/m	IP	COLOR	Tº COLOR (°K)	CORTE (A)	LED/m	ÁNGULO	DIMENSIONES (mm)	CORTE MIN. (mm)
CINTALED01	3528 SMD	4,8	20	ww	2700-3300	0,35	60	120º	5000x10x2,2	50
CINTALED02	3528 SMD	4,8	20	nw	4000-4500	0,35	60	120º	5000x10x2,2	50
CINTALED03	3528 SMD	4,8	20	cw	6000	0,35	60	120º	5000x10x2,2	50
CINTALED04	3528 SMD	4,8	65	ww	2700-3300	0,35	60	120º	5000x10x2,2	50
CINTALED05	3528 SMD	4,8	65	nw	4000-4500	0,35	60	120º	5000x10x2,2	50
CINTALED06	3528 SMD	4,8	65	cw	6000	0,35	60	120º	5000x10x2,2	50
CINTALED07	5050 SMD	14,4	20	ww	2700-3300	1,2	60	120º	5000x12x2,2	50
CINTALED08	5050 SMD	14,4	20	nw	4000-4500	1,2	60	120º	5000x12x2,2	50
CINTALED09	5050 SMD	14,4	20	cw	6000	1,2	60	120º	5000x12x2,2	50
CINTALED10	5050 SMD	14,4	65	ww	2700-3300	1,2	60	120º	5000x12x2,2	50
CINTALED11	5050 SMD	14,4	65	nw	4000-4500	1,2	60	120º	5000x12x2,2	50
CINTALED12	5050 SMD	14,4	65	cw	6000	1,2	60	120º	5000x12x2,2	50

CÓDIGO	DESCRIPCIÓN
DRIVER01	Driver IP20 12V/30W
DRIVER02	Driver IP20 12V/60W
DRIVER03	Driver IP20 12V/100W
DRIVER04	Driver IP65 12V/30W
DRIVER05	Driver IP65 12V/60W
DRIVER06	Driver IP65 12V/100W